

Colortone Range



Available in Dune eVo, Fine Fissured or Neeva surfaces depending on your acoustic requirements, the Colortone Range offers a simple way to add darker tones and more depth to your ceilings. Combine the black colour option with Prelude 24 black grid for the perfect solution for cinema applications and other dark spaces.

KEY FEATURES

- 3 edge details available (Dune eVo)
- Excellent acoustical absorption:
1.00 α_w (Neeva)
- Available in black (Fine Fissured & Neeva) and Platinum (Dune eVo)


APPLICATION AREAS

Ideal for cafeterias, cinemas, theatres.



EDGE DETAIL	BOARD																																												
																																													
THICKNESS (MM)	15																																												
MODULES (MM)	600 x 600 2695DBK 1200 x 600 2696MBK																																												
SUSPENSION SYSTEMS	Prelude 24 XL ² / TLS Prelude 24 CR / TLS Prelude 24 Sixty ² XL ² / TLS																																												
COLOURS	 Black (BK)																																												
SUSTAINABILITY	 20		 A	 E1																																									
ACOUSTICS	<table><tr><td rowspan="3"> EN ISO 20140-9 & EN ISO 717-1</td><td rowspan="3"> EN ISO 140-3 & EN ISO 717-1</td><td rowspan="3"> EN ISO 354 & EN ISO 11654</td><td colspan="8">Hz α_p</td></tr><tr><td>D_{nfw}</td><td>R_w</td><td>α_w</td><td>Class</td><td>NRC</td><td>125</td><td>250</td><td>500</td><td>1000</td><td>2000</td><td>4000</td></tr><tr><td>Board 15</td><td>-</td><td>7 dB</td><td>1.00</td><td>A</td><td>0.95</td><td>0.40</td><td>0.90</td><td>1.00</td><td>0.90</td><td>1.00</td><td>1.00</td></tr></table>											 EN ISO 20140-9 & EN ISO 717-1	 EN ISO 140-3 & EN ISO 717-1	 EN ISO 354 & EN ISO 11654	Hz α_p								D _{nfw}	R _w	α_w	Class	NRC	125	250	500	1000	2000	4000	Board 15	-	7 dB	1.00	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00
 EN ISO 20140-9 & EN ISO 717-1	 EN ISO 140-3 & EN ISO 717-1	 EN ISO 354 & EN ISO 11654	Hz α_p																																										
			D _{nfw}	R _w	α_w	Class	NRC	125	250	500	1000				2000	4000																													
			Board 15	-	7 dB	1.00	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00																															
FIRE REACTION	 EEA Euroclass A1 EN 13501-1																																												
OTHER PERFORMANCES & FEATURES	 EN 12667 & ISO 8301 $\lambda = 0.033$ W/m K	 95% RH  1.2 kg/m²		 30 YEAR SYSTEM GUARANTEE	 BIM READY																																								

EDGE DETAIL	BOARD																																										
																																											
THICKNESS (MM)	15																																										
MODULES (MM)	600 x 600 9121MBK																																										
SUSPENSION SYSTEMS	Prelude 24 XL ² / TLS Prelude 24 CR / TLS Prelude 24 Sixty ² XL ² / TLS																																										
COLOURS	 Black (BK)																																										
SUSTAINABILITY	 51		 A	 E1																																							
ACOUSTICS	<table><tr><td rowspan="2">  EN ISO 10848-2 & EN ISO 717-1 </td><td rowspan="2">  EN ISO 354 & EN ISO 11654 </td><td colspan="9">Hz α_p</td></tr><tr><td>D_{nfw}</td><td>α_w</td><td>Class</td><td>NRC</td><td>125</td><td>250</td><td>500</td><td>1000</td><td>2000</td><td>4000</td></tr><tr><td>Board</td><td>36 dB</td><td>0.60 (H)</td><td>C</td><td>0.60</td><td>0.40</td><td>0.40</td><td>0.55</td><td>0.75</td><td>0.75</td><td>0.75</td></tr></table>											 EN ISO 10848-2 & EN ISO 717-1	 EN ISO 354 & EN ISO 11654	Hz α_p									D_{nfw}	α_w	Class	NRC	125	250	500	1000	2000	4000	Board	36 dB	0.60 (H)	C	0.60	0.40	0.40	0.55	0.75	0.75	0.75
 EN ISO 10848-2 & EN ISO 717-1	 EN ISO 354 & EN ISO 11654	Hz α_p																																									
		D_{nfw}	α_w	Class	NRC	125	250	500	1000	2000	4000																																
Board	36 dB	0.60 (H)	C	0.60	0.40	0.40	0.55	0.75	0.75	0.75																																	
FIRE REACTION	 EEA Euroclass A2-s1, d0 EN 13501-1																																										
OTHER PERFORMANCES & FEATURES	 EN 12667 & ISO 8301 $\lambda = 0.060$ W/m K	 95% RH  3.4 kg/m²		 30 YEAR SYSTEM GUARANTEE	 BIM READY																																						

EDGE DETAIL	BOARD		TEGULAR		MICROLOOK 90																												
																																	
THICKNESS (MM)	15		15		15																												
MODULES (MM)	600 x 600 5460MPN 1200 x 600 5461MPN		600 x 600 5462MPN		600 x 600 5464MPN																												
SUSPENSION SYSTEMS	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette XL ²																												
COLOURS	 Platinum (PN)																																
SUSTAINABILITY	 44   A  EN 13964 E1																																
ACOUSTICS	 EN ISO 10848-2 & EN ISO 717-1  EN ISO 354 & EN ISO 11654 <table><tr><th></th><th>D_{nfw}</th><th>α_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr><tr><td>Board, Tegular, MicroLook 90</td><td>34 dB</td><td>0.60(H)</td><td>C</td><td>0.50</td><td>0.40</td><td>0.40</td><td>0.60</td><td>0.55</td><td>0.55</td><td>0.50</td></tr></table>												D _{nfw}	α _w	Class	NRC	125	250	500	1000	2000	4000	Board, Tegular, MicroLook 90	34 dB	0.60(H)	C	0.50	0.40	0.40	0.60	0.55	0.55	0.50
	D _{nfw}	α _w	Class	NRC	125	250	500	1000	2000	4000																							
Board, Tegular, MicroLook 90	34 dB	0.60(H)	C	0.50	0.40	0.40	0.60	0.55	0.55	0.50																							
FIRE REACTION	 EEA Euroclass A2-s1, d0 EN 13501-1																																
OTHER PERFORMANCES & FEATURES	 Up to 72%  95% RH   30 YEAR SYSTEM GUARANTEE  λ = 0.060 W/m K EN 12667 & ISO 8301  3.6 kg/m²   BIM READY																																